

551289

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
14 October 2004 (14.10.2004)


PCT

(10) International Publication Number
WO 2004/086992 A1

- (51) International Patent Classification⁷: **A61B 18/14**
- (21) International Application Number:
PCT/US2004/009610
- (22) International Filing Date: 29 March 2004 (29.03.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/458,489 28 March 2003 (28.03.2003) US
60/458,490 28 March 2003 (28.03.2003) US
60/458,491 28 March 2003 (28.03.2003) US
60/458,643 28 March 2003 (28.03.2003) US
60/458,856 28 March 2003 (28.03.2003) US
- (71) Applicant (for all designated States except US): **C.R. BARD, INC.** [US/US]; 730 Central Avenue, Murray Hill, NJ 07974 (US).
- (72) Inventor; and
(75) Inventor/Applicant (for US only): **STEVENS-WRIGHT, Debbie** [US/US]; 175 Candlestick Road, North Andover, MA 01845 (US).
- (74) Agent: **MORRIS, James, H.**; Wolf, Greenfield & Sacks, P.C., 600 Atlantic Avenue, Boston, MA 02210 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: JUNCTION OF CATHETER TIP AND ELECTRODE



(57) Abstract: Junctions of ablation electrodes and catheters are disclosed. Electrophysiology catheter systems include a recessed region such as a channel at a junction of an electrode and a catheter shaft. The channel can help to reduce electrode hotspots, energy density and/or blood coagulation at the junction. The channel may be incorporated in a distal tip electrode or a ring electrode.

WO 2004/086992 A1